

## § 1223.1

### § 1223.1 Scope.

This part establishes a consumer product safety standard for infant swings.

### § 1223.2 Requirements for infant swings.

(a) Except as provided in paragraph (b) of this section, each infant swing must comply with all applicable provisions of ASTM F2088—12a, Standard Consumer Safety Specification for Infant Swings, approved on September 1, 2012. The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. You may obtain a copy from ASTM International, 100 Bar Harbor Drive, P.O. Box 0700, West Conshohocken, PA 19428; <http://www.astm.org>. You may inspect a copy at the Office of the Secretary, U.S. Consumer Product Safety Commission, Room 820, 4330 East West Highway, Bethesda, MD 20814, telephone 301-504-7923, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: [http://www.archives.gov/federal\\_register/code\\_of\\_federal\\_regulations/ibr\\_locations.html](http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html).

(b)(1) Instead of complying with section 8.3.1 of ASTM F2088—12a, comply with the following:

(i) 8.3.1 The warning statements shall address the following at a minimum:

(ii) 8.3.1.1 Products having an adjustable seat recline with a maximum seatback angle greater than 50 degrees from horizontal measured in accordance with 7.13 shall address the following:

Keep swing seat fully reclined until child is at least 4 months old AND can hold up head without help. Young infants have limited head and neck control. If seat is too upright, infant's head can drop forward, compress the airway, and result in DEATH.

(iii) 8.3.1.2 To prevent serious injury or death from infants falling or being strangled in straps:

(A) Always secure infant in the restraint system provided.

(B) Never leave infant unattended in swing.

## 16 CFR Ch. II (1–13 Edition)

(C) Discontinue use of swing when infant attempts to climb out.

(D) Travel swings (see 3.1.11) shall address the following:

Always place swing on floor. Never use on any elevated surface.

(2) Instead of complying with section 7.12.2 of ASTM F2088—12a, comply with the following:

(i) 7.12.2 Place the back of the swing in the most upright position. Remove positioning accessories, including pillows. Position the segments of the restraint system to limit interaction with the Hinged Weight Gage—Infant (see Fig. 10) when placed in the seat. Place the Hinged Weight Gage—Infant with the hinge located at the junction of the swing back and seat bottom (see Fig. 8). Determine if the lowest point of the toy positioned over the occupant is within 25.25 in. (641.5 mm) of the top surface of the Lower Plate (see Fig. 10)—throughout the swing seat's range of motion. Proceed to 7.12.3 if the distance is 25.25 in. (641.5 mm) or less. The toy is considered out of reach and not tested to 7.12.3 if the distance is greater than 25.25 in. (641.5 mm).

(ii) [Reserved]

## PART 1224—SAFETY STANDARD FOR PORTABLE BED RAILS

Sec.

1224.1 Scope, application, and effective date.

1224.2 Requirements for portable bed rails.

AUTHORITY: Sections 3 and 104 of Pub. L. 110-314, 122 Stat. 3016 (August 14, 2008).

SOURCE: 77 FR 12197, Feb. 29, 2012, unless otherwise noted.

### § 1224.1 Scope, application, and effective date.

This part establishes a consumer product safety standard for portable bed rails manufactured or imported on or after August 29, 2012.

### § 1224.2 Requirements for portable bed rails.

(a) Each portable bed rail as defined in ASTM F2085—12, *Standard Consumer Safety Specification for Portable Bed Rails*, approved January 1, 2012, must comply with all applicable provisions of ASTM F2085—12. The Director of the Federal Register approves this incorporation by reference in accordance with